



FARM WAGONS

From 5 to 15 Ton
Loading Capacities

9 MODELS TO CHOOSE FROM

HEAVY DUTY - BUILT TO LAST

Double Reach - Proven better for years!
Flexible and Strong

PRO-SERIES 5 TON WAGON

Model RS50 SPECIFICATIONS



Axles	4" x 3" .188 Wall
Spindle	1-3/4"
Hub	5 Bolt
Hub Capacity	2500 lb.
Bearings	Taper Roller
Steering Rod	7/8"
Tongue	Quick Hitch
Reach	2-3/8" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	78"
Approx. Weight	450 lbs.

PRO-SERIES 8 TON WAGON

Model RS80 SPECIFICATIONS



Axles	5" x 3" .188 Wall
Spindle	1-3/4"
Hub	6 Bolt
Hub Capacity	4000 lb.
Bearings	Taper Roller
Steering Rod	1"
Tongue	Quick Hitch
Reach	3" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	78"
Approx. Weight	570 lbs.

PRO-SERIES 10 TON WAGON

Model RS105 SPECIFICATIONS



Axles	6" x 3" .188 Wall
Spindle	2"
Hub	6 Bolt
Hub Capacity	5000 lb.
Bearings	Taper Roller
Steering Rod	1"
Tongue	Quick Hitch
Reach	3" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	78"
Approx. Weight	610 lbs.

STEERING PINS – Tapered pin with slotted nuts so you can tighten steering again and again.

TIE ROD ENDS – Tapered, hardened bronze bushings with dust cap to keep dirt out.

WHEEL BASE – 15' wheel base standard or varied length on request.

Wide variety of wheels and tires

DISTRIBUTED BY:



www.walcoequipment.com

HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9

TEL: (519) 669-4025 FAX: (519) 669-1436

ORDER DESK

e-mail: orders@walcoequipment.com

TEL: (519) 669-1401 FAX (519) 669-3499

QUEBEC OFFICE

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC JOC

TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcogc@walcoequipment.com

WALCO USA

4469 292nd St. E. Box 57 Randolph MN 55065

Tel: (507) 663-9090 Fax (507) 663-0999

PRO-SERIES 11 TON WAGON**Model RS110 SPECIFICATIONS**

Axles	6" x 3" .188 Wall
Spindle	2-1/4"
Hub	8 Bolt
Hub Capacity	6500 lb.
Bearings	Taper Roller
Steering Rod	1"
Tongue	Quick Hitch
Reach	3" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	78"
Approx. Weight	685 lbs.

PRO-SERIES 12 TON TANDEM WAGON**Model RS120T SPECIFICATIONS**

Axles	6" x 3" .188 Wall
Spindle	2-1/4" Front 2-1/4" Rear
Hub	6 or 8 Bolt
Hub Capacity	5000 lb.
Bearings	Taper Roller
Steering Rod	1"
Tongue	Quick Hitch
Reach	3" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	78"
Approx. Weight	990 lbs.

PRO-SERIES 13 TON WAGON**Model RS130 SPECIFICATIONS**

Axles	8" x 4" .188 Wall
Spindle	2-1/2"
Hub	8 Bolt
Hub Capacity	8000 lb.
Bearings	Taper Roller
Steering Rod	1-1/8"
Tongue	Quick Hitch
Reach	3-1/2" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	86"
Approx. Weight	815 lbs.

PRO-SERIES 14 TON TANDEM WAGON**Model RS140T SPECIFICATIONS**

Axles	8" x 4" .188 Wall
Spindle	2-1/4" Front 2-1/2" Rear
Hub	8 Bolt
Hub Capacity	6500 lb.
Bearings	Taper Roller
Steering Rod	1-1/8"
Tongue	Quick Hitch
Reach	3-1/2" O.D. .188 Wall
Stakes	38" - 42" Adjustable
Track	86"
Approx. Weight	1570 lbs.

STEERING PINS – Tapered pin with slotted nuts so you can tighten steering again and again.

TIE ROD ENDS – Tapered, hardened bronze bushings with dust cap to keep dirt out.

WHEEL BASE – 15' wheel base standard or varied length on request.

Wide variety of wheels and tires

DISTRIBUTED BY:



www.walcoequipment.com

HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9

ORDER DESK

TEL: (519) 669-4025 FAX: (519) 669-1436

e-mail: orders@walcoequipment.com

QUEBEC OFFICE

TEL: (519) 669-1401 FAX (519) 669-3499

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC JOC

TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcoqc@walcoequipment.com

WALCO USA

4469 292nd St. E. Box 57 Randolph MN 55065

Tel: (507) 663-9090 Fax (507) 663-0999

PRO-SERIES 15 TON WAGON

Model RS150 SPECIFICATIONS



Axles	8" x 4" .250 Wall
Spindle	2-3/4"
Hub	8 Bolt
Hub Capacity	8000 lb.
Bearings	Taper Roller
Steering Rod	1-1/4"
Tongue	Quick Hitch
Reach	3-1/2" O.D. .188 Wall
Stakes	42" Fixed
Track	86"
Approx. Weight	1560 lbs.



Bronze Bushings with Rubber O-Rings on King Pins and Tongue. Keeps out Dirt and Moisture.



Tapered Roller Bearings on tongue pivot for smoother turning and better trailing. eliminates swaying on road.



Tapered stainless steel steering pins and hardened bronze bushings give you the option of tightening the steering repeatedly.

PRO-SERIES COMBINE HEADER

Agrimaster



Model RS70HC SPECIFICATIONS

Axles	4" x 3" .188 Wall
Spindle	1-3/4"
Hub	6 Bolt
Hub Capacity	4000 lb.
Bearings	Taper Roller
Steering Rod	7/8"
Tongue	Quick Hitch
Reach	2-3/8" O.D. .188 Wall
Stakes	N/A
Track	84"
Weight	1180 lbs. Approx.



STEERING PINS – Tapered pin with slotted nuts so you can tighten steering again and again.
TIE ROD ENDS – Tapered, hardened bronze bushings with dust cap to keep dirt out.
WHEEL BASE – 15' wheel base standard or varied length on request. Wide variety of wheels and tires

DISTRIBUTED BY:



www.walcoequipment.com

HEAD OFFICE

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9
 TEL: (519) 669-4025 FAX: (519) 669-1436

ORDER DESK

e-mail: orders@walcoequipment.com
 TEL: (519) 669-1401 FAX (519) 669-3499

QUEBEC OFFICE

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC J0C
 TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcoqc@walcoequipment.com

WALCO USA

4469 292nd St. E. Box 57 Randolph MN 55065
 Tel: (507) 663-9090 Fax (507) 663-0999