

Introducing a revolutionary auger that maximizes versatility...

- ▣ Load or unload with one auger
- ▣ Transfer from totes, grain bins or gravity wagons

360°

FLEX ARM III



▲ Unload



◀ Load



▲ Transport



304 Stainless Steel

Features and Specifications

- Size: 6" x 12', 14' or 16'
- Flighting: cupped or bristle
- Durable stainless construction also available as a black powder-coated unit
- Adjustable hopper fits most gravity boxes
- 4' flex or 3-stage telescopic spout
- Single rope spring return valve
- 5.9 cubic inch hydraulic motor
- UHMW bushing supports bottom of auger flighting
- Adapter available for dual boxes
- Removable end cap for easy cleanout

Standard Auger

Length: 12', 14' or 16'



Flex Arm III Features

Size: 6" x 17' | Available in: 304 Stainless Steel or as a black steel powder coated unit | Flighting: cupped or bristle
 Spout: 3-stage telescopic or 4' flex | Single rope spring return valve
 Motor: 5.9 cubic inch hydraulic | Spout adapter for quick disconnect

and Specifications



www.walcoequipment.com

HEAD OFFICE

ORDER DESK

QUEBEC OFFICE

WALCO USA

20 ARTHUR STREET NORTH, ELMIRA, ONTARIO N3B 1Z9

TEL: (519) 669-4025 FAX: (519) 669-1436

e-mail: orders@walcoequipment.com

TEL: (519) 669-1401 FAX (519) 669-3499

364 RTE.122 ST.GERMAIN DE GRANTHAM, QUÉBEC J0C

TEL: (819) 395-5115 Fax (819) 395-2624

e-mail: walcoqc@walcoequipment.com

4469 292nd St. E. Box 57 Randolph MN 55065

Tel: (507) 663-9090 Fax (507) 663-0999